

Chain kit component

Patent Number: GB2073363

Publication date: 1981-10-14

Inventor(s):

Applicant(s):: RUD KETTEN RIEGER & DIETZ

Requested
Patent:

☐ GB2073363

Application
Number:

GB19810009080 19810324

Priority Number
(s):

DE19803012886 19800331

IPC

Classification: F16G15/06

EC

Classification: F16G15/06

Equivalents:

☐ AT135481, ☐ AT387076B, ☐ DE3012886, ☐ FR2479392, JP1481037C, ☐
JP57006104, JP63027566B, ☐ SE449513, SE8101433

Abstract

A component which belongs to a series of matched sets of parts for a chain system is provided with a connection head (1) which has an insertion slot (2) and a holding bolt (4) bridging this slot (2). The widths of the insertion slots (2), the diameters of the holding bolts (4), the bar diameters (d_n , $d_{n\{1\}}$) and the internal widths of the chain links (3) of the kit are varied stepwise such as to prevent combinations of links (3) and connecting members which are incompatible. To eliminate the risk of using a holding bolt (4) which is too small for a certain component, each component is provided with a stepped bore (5, 6) the smallest diameter D_{min} of which is greater than the diameter of a holding bolt (4) of the set of parts of the next

smaller size.



Data supplied from the esp@cenet database - I2

(21) Application No 8109080

(22) Date of filing
24 Mar 1981

(30) Priority data

(31) 3012886

(32) 31 Mar 1980

(33) Fed Rep of Germany
(DE)

(43) Application published
14 Oct 1981

(51) INT CL³ F16G 15/06

(52) Domestic classification
F2Q 53

(56) Documents cited
GB 1493095

(58) Field of search
F2Q

(71) Applicant
RUD-Kettenfabrik Rieger
& Dietz GmbH u Co
7080 Aalen 1
Federal Republic of
Germany

(72) Inventor
Werner Rieger

(74) Agents
Bromhead & Co
30 Cursitor Street
Chancery Lane
London EC4A 1LT

(54) Chain kit component

(57) A component which belongs to a series of matched sets of parts for a chain system is provided with a connection head (1) which has an insertion slot (2) and a holding bolt (4) bridging this slot (2). The widths of the insertion slots (2), the diameters of the holding bolts (4), the bar diameters (d_n , d_{n-1}) and the internal widths of the chain links (3) of the kit are varied stepwise such as to prevent combinations of links (3) and connecting members which are incompatible. To eliminate the risk of using a holding bolt (4) which is too small for a certain component, each component is provided with a stepped bore (5, 6) the smallest diameter D_{min} of which is greater than the diameter of a holding bolt (4) of the set of parts of the next smaller size.




Fig. 1




Fig. 1

2/2

